



TECHNICAL DATA SHEET

AD-Tec 10 0W-30 V

5 Litre, 20 Litre & 199 Litre

Product Description

AD-TEC 10 0W/30 V is a fully synthetic engine oil formulated to meet the performance demands of modern petrol and diesel engines. AD-TEC 10 0W/30 V is a blend of the very latest in base oil and additive technology, designed for extended drain performance, especially suited for modern Volvo engines both petrol and diesel.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A5/B5

API: SL/CF

Volvo: VCC 95200377



* Image for illustrative purposes only.

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification and viscosity of lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep upright and sealed in a cool, dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Size	Part No	Barcode
5 Litre	AED005	5020618202042
20 Litre	AED020	5020618202790
199 Litre	AED199	5020618203087

Revision: 1 | Date: 27/04/2022



TECHNICAL DATA SHEET

AD-Tec 10 0W-30 V

5 Litre, 20 Litre & 199 Litre

Percentage of Base Oil : More Than 70%

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	9.99
Total Base Number	ASTM D2896	mg KOH/g	8		10.62
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		13	
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			53.87
Density	ASTM D792	@ 15°C			0.845
Pour Point	ASTM D97	°C		-40	

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 27/04/2022