



TECHNICAL DATA SHEET

AD-Tec 30 10W/30

20 Litre

Product Description

AD-Tec 30 10W-30 is a superior mineral engine oil formulated to increase engine protection during cold start up thereby reducing engine wear. AD-Tec 30 10W-30 is a low viscosity engine oil that can help to improve fuel economy and engine cleanliness.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A2/B2 & E2

API: SL/CF

Ford: WSS-M2C909-A

MB: 229.1

VW: 505.00



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	ABE020	5020618203018

Product Benefits

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Suitable for petrol and diesel engines
- * Outstanding engine cleanliness and sludge control

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber Liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Revision: 1 | Date: 11/03/2024



TECHNICAL DATA SHEET

AD-Tec 30 10W/30

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.9
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		12.12
Pour Point	ASTM D97	°C		-30	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			69.24
Density	ASTM D792	@ 15°C			0.869
Viscosity Index	ASTM D2270				147.777

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.