

Page 1 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.09.2023 / 0015
Replacing version dated / version: 01.11.2021 / 0014
Valid from: 27.09.2023
PDF print date: 29.09.2023
Lenkgetriebeoel 3100

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lenkgetriebeoel 3100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Gear lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment.

P501-Dispose of contents / container to an approved waste disposal facility.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Page 2 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Distillates (petroleum), solvent-dewaxed light paraffinic	
Registration number (REACH)	01-2119480132-48-XXXX
Index	649-469-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	265-159-2
CAS	64742-56-9
content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated light naphthenic	
Registration number (REACH)	01-2119480375-34-XXXX
Index	649-466-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	265-156-6
CAS	64742-53-6
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Baseoil - unspecified *	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	---
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

1-(tert-dodecylthio)propan-2-ol	
Registration number (REACH)	01-2119953277-30-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	266-582-5
CAS	67124-09-8
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	Skin Sens. 1B, H317: >=14,2001 %

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	
Registration number (REACH)	01-2119510877-33-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	620-540-6
CAS	1218787-32-6
content %	0,01-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)

Ethanol	
Registration number (REACH)	---
Index	603-002-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	200-578-6
CAS	64-17-5

Page 3 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

content %	<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	Eye Irrit. 2, H319: >=50 %

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP, REACH-IT List-No.	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

Oil acne

Sensitive individuals:

Allergic reaction possible.

On vapour formation:

Irritation of the respiratory tract

Ingestion:

Gastrointestinal disturbances

Nausea

Vomiting

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.09.2023 / 0015
Replacing version dated / version: 01.11.2021 / 0014
Valid from: 27.09.2023
PDF print date: 29.09.2023
Lenkgetriebeoel 3100

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Foam

Dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

Oxides of phosphorus

Toxic pyrolysis products.

Flammable vapour/air mixtures

Hydrogen sulphide

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid formation of oil mist.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Oil binder

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

GB

Page 5 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

Avoid formation of oil mist.
 Ensure good ventilation.
 Keep away from sources of ignition - Do not smoke.
 Do not heat to temperatures close to flash point.
 Avoid contact with eyes.
 Avoid long lasting or intensive contact with skin.
 Do not carry cleaning cloths soaked in product in trouser pockets.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Impermeable floor.
 Protect against moisture and store closed.
 Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.
 Observe the instructions for good working practice and the recommendations for risk assessment.
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Ethanol		
WEL-TWA: 1000 ppm (1920 mg/m3)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Alcohol 25/a Ethanol (81 01 631) - Compur - KITA-104 SA (549 210) DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) - DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013 - EU project - BC/CEN/ENTR/000/2002-16 card 63-2 (2004) DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013 - EU project - BC/CEN/ENTR/000/2002-16 card 63-2 (2004)		
BMGV: ---	Other information: ---		
Chemical Name	Oil mist, mineral		
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---		

Distillates (petroleum), solvent-dewaxed light paraffinic

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	

Distillates (petroleum), hydrotreated light naphthenic

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note

Page 6 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

	Environment - oral (animal feed)		PNEC	9,33	mg/kg	
Industrial	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg	
Industrial	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3	
Industrial	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg	

Baseoil - unspecified						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3	

1-(tert-dodecylthio)propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	0,244	mg/kg	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, marine		PNEC	0,828	mg/kg	
	Environment - sediment, freshwater		PNEC	8,28	mg/kg	
	Environment - marine		PNEC	0,001	mg/l	
	Environment - freshwater		PNEC	0,006	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,84	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,9	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,67	mg/kg body weight/day	
Consumer	Human - dermal	Short term, local effects	DNEL	0,1077	mg/cm2	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,34	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	11,8	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,2154	mg/cm2	

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,21	µg/l	

Page 7 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

Consumer	Human - dermal	Long term, systemic effects	DNEL	0,21	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,21	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,3	mg/kg bw/d	

Ethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,75	mg/l	
	Environment - sewage treatment plant		PNEC	580	mg/l	
	Environment - sediment, freshwater		PNEC	3,6	mg/kg dry weight	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m ³	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Page 8 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.09.2023 / 0015
Replacing version dated / version: 01.11.2021 / 0014
Valid from: 27.09.2023
PDF print date: 29.09.2023
Lenkgetriebeoel 3100

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Protective gloves, oil resistant (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective PVC gloves (EN ISO 374).

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Liquid

Colour:

Brown

Odour:

Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

Flammability:

Flammable

Lower explosion limit:

There is no information available on this parameter.

Page 9 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

Upper explosion limit:	There is no information available on this parameter.
Flash point:	200 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	35 mm ² /s (40°C)
Kinematic viscosity:	7 mm ² /s (100°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,87 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Protect from humidity.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Lenkgetriebeoel 3100						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), solvent-dewaxed light paraffinic

Page 10 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:	NOAEL	>1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Reproductive toxicity:	NOAEL	>2000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., vomiting, nausea

Distillates (petroleum), hydrotreated light naphthenic

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Aspiration hazard:						Yes

Baseoil - unspecified

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin sensitisation:						Not sensitizing, Analogous conclusion
Aspiration hazard:						Yes

Page 11 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

Symptoms:						mucous membrane irritation
-----------	--	--	--	--	--	----------------------------

1-(tert-dodecylthio)propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1500	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1C
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	51-124,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	>3000	mg/kg	Rat	OECD 451 (Carcinogenicity Studies)	24 mon

Page 12 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

Reproductive toxicity:	NOAEL	5200	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAL	>20	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Male
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1730	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Female
Symptoms:						respiratory distress, drowsiness, unconsciousness , drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea

11.2. Information on other hazards

Lenkgetriebeoel 3100						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:						Excessive alcohol consumption during pregnancy induces the foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative absorption., Experiences on persons.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Lenkgetriebeoel 3100

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Distillates (petroleum), solvent-dewaxed light paraffinic

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	LL50	48h	>1000	mg/l	Gammarus sp.	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Inherent
12.3. Bioaccumulative potential:	Log Pow		>3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Distillates (petroleum), hydrotreated light naphthenic

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 14 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	> 100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable., Mechanical precipitation possible.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

Baseoil - unspecified

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

1-(tert-dodecylthio)propan-2-ol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,75	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	0,56	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,58	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	0,32	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	21d	0,75	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	

Page 15 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeöl 3100

12.1. Toxicity to algae:	NOEC/NOEL	96h	100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	5,9	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Kow		5,7				
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,1	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	0,043	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC10	21d	0,0107	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	0,0538	mg/l	Pseudokirchneriella subcapitata	IUCLID Chem. Data Sheet (ESIS)	Analogous conclusion
12.2. Persistence and degradability:		28d	63	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable, Analogous conclusion
12.2. Persistence and degradability:		28d	75	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		3,6				Low
12.3. Bioaccumulative potential:	BCF		110,2				calculated
Toxicity to bacteria:	EC50	3h	167	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

Ethanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short-term Toxicity Test on Embryo and Sac-fry Stages)	

Page 16 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

12.1. Toxicity to daphnia:	EC50	48h	5414	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	97	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		(-0,35) - (-0,32)				Bioaccumulation is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				
12.4. Mobility in soil:	H (Henry)		0,000138				
12.4. Mobility in soil:	Koc		1,0				Highestimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	
Other information:	COD		1,9	g/g			
Other information:	BOD5		1	g/g			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Untamminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Page 17 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable

Transport by sea (IMDG-code)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	Not applicable

Transport by air (IATA)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):	1,581 %
-----------------------------	---------

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:	3, 8, 11, 12
-------------------	--------------

These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H314 Causes severe skin burns and eye damage.
 H225 Highly flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Asp. Tox. — Aspiration hazard
 Skin Sens. — Skin sensitization
 Aquatic Acute — Hazardous to the aquatic environment - acute
 Acute Tox. — Acute toxicity - oral
 Skin Corr. — Skin corrosion
 Eye Dam. — Serious eye damage
 Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon

Page 19 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.09.2023 / 0015
 Replacing version dated / version: 01.11.2021 / 0014
 Valid from: 27.09.2023
 PDF print date: 29.09.2023
 Lenkgetriebeoel 3100

dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 TOC Total organic carbon
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are

GB

Page 20 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.09.2023 / 0015
Replacing version dated / version: 01.11.2021 / 0014
Valid from: 27.09.2023
PDF print date: 29.09.2023
Lenkgetriebeoel 3100

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax:
+49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document
is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.