

Fully Synthetic Gear Oil (GL5) SAE 75W-90

Description

Our fully synthetic gear oil is a high-performance, high-pressure gear oil for high-load manual, auxiliary, transaxle and hypoid transmissions which require a lubricant according to API GL 5. High-quality, fully synthetic base oils and modern additive technology guarantee a wide application range for this oil as well as optimum transmission lubrication under extreme conditions.

Properties

- distinctive high-pressure characteristics
- excellent wear protection
- reduces gearshift resistance
- outstanding viscosity stability
- reduces transmission noise
- outstanding corrosion protection

Approvals

API GL5 • MIL-L 2105 C • MIL-L 2105 D

Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	80 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	185 DIN ISO 2909
Pour point	-57 °C DIN ISO 3016
Flash point	190 °C DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

Areas of application

For extremely high-load manual, auxiliary, transaxle and hypoid transmissions.

Application

The requirements of the vehicle and transmission manufacturers must be adhered to. Miscible with any mineral-base oil residues remaining during oil changes in transmissions and axle drives. Must be disposed of with standard used oil.

Available pack sizes

Available pack sizes

500 ml Can plastic	1413 D-GB-I-E-P
1 l Can plastic	1414 D-GB-I-E-P
1 l Can plastic	2183 D-PL-H-RO-TR
1 l Can plastic	8967 D-NL-F-GR-ARAB
20 l Canister plastic	1415 D-GB-I-E-P
60 l Drum sheet metal	1412 D-GB
205 l Drum sheet metal	1411 D-GB



Our information is based on thorough research and may be considered reliable, although not legally binding.