

## Top Tec MTF 5400 75W-90

### Description

Versatile transmission fluid based on synthetic technology. Offers large power reserves and exceeds the high test requirements of renowned vehicle manufacturers. Ensures that assemblies function perfectly, even under the most extreme operating conditions and when exposed to large temperature fluctuations. Reliable lubrication, optimum protection against wear and reduced transmission noise. Allows long oil change intervals.

### Properties

- excellent viscosity/temperature properties
- outstanding seal compatibility
- excellent resistance to aging
- excellent wear resistance
- high pressure-absorption capability
- wide viscosity range
- reduces gearshift resistance
- excellent corrosion protection
- reduces transmission noise

### Specifications / Approvals

API GL4

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

BMW MTF LT-4 • Ford ESD-M2C 175-A • Ford ESD-M2C 186-A • Ford WSD-M2C 200-C • MB 235.72 • VW 501 50 • VW G 005 000 • VW G 052 145 • VW G 052 157 • VW G 052 190 • VW G 052 911 • VW G 50 • VW G 51

### Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,880 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	88,0 mm <sup>2</sup> /s ASTM D7042
Viscosity at 100 °C	15,5 mm <sup>2</sup> /s ASTM D7042
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D2983
Viscosity index	185 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	180 °C DIN ISO 2592



### Technical data

Color number (ASTM)	L 1,5
	DIN ISO 2049

### Areas of application

For use in high-load manual, transaxle, auxiliary and differential transmissions. Especially recommended for use in vehicles from Audi, BMW, Ford, Mercedes-Benz, Seat, Škoda and Volkswagen, as well as for vehicles from other manufacturers.

### Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

### Available pack sizes

1 l Can plastic	21791 D-GB-I-E-P
20 l Canister plastic	21792 D-GB-I-E-P
60 l Black plate barrel	21793 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**