

Top Tec 6310 0W-20



Description

Premium low-friction motor oil. Ensures optimum lubrication and outstanding lubricating film stability as well as minimum wear and the smallest deposits even under extreme loads. Ideally suited for engines with start/stop system. Guarantees maximum performance with low fuel consumption.

Properties

- smooth engine running
- outstanding engine cleanliness
- excellent wear protection
- high lubrication reliability
- saves fuel and reduces pollutant emissions
- high shear stability
- optimum stability to aging
- excellent high and low temperature behavior
- long engine service life
- optimum oil pressure under all operating conditions
- tested for turbochargers and catalytic converters

Specifications / Approvals

ACEA C5, C6 • API SP • Peugeot Citroen (PSA) B71 2010

Technical data

SAE class (engine oils)	0W-20 SAE J 300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	41,0 mm ² /s ASTM D7042
Viscosity at 100 °C	8,1 mm ² /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	11,5 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	9,8 mg KOH/g DIN ISO 3771

Technical data

Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049
Oil base	Advanced Full Synthetic

Areas of application

For gasoline, diesel and hybrid engines. Specially developed for the requirements in PSA Pure Tech and BlueHDi engines from model year 2018 such as EB2xx, DV5Rxx from OPR 16886 (see ORGA calculator), which are also installed in vehicles from Citroën, DS, Fiat, Jeep, Opel and Peugeot, among others. Can also be used in engines from other manufacturers.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21880 BOOKLET
5 l Canister plastic	21882 BOOKLET
20 l Canister plastic	21877 D-GB-I-E-P
60 l Black plate barrel	21878 D-GB
205 l Black plate barrel	21879 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.