

Leichtlauf Performance 10W-40



Description

Low-friction motor oil for gasoline and diesel engines, with and without exhaust gas turbocharging and charge air cooler. Protects against wear, reduces oil and fuel consumption and ensures fast oil penetration of the engine.

Properties

- high lubrication reliability
- high shear stability
- instant lubrication after cold start
- optimum stability to aging
- excellent high and low temperature behavior
- smooth engine running
- outstanding engine cleanliness
- miscible with all commercially available motor oils
- saves fuel and reduces pollutant emissions
- high wear resistance
- tested for turbochargers and catalytic converters

Specifications / Approvals

ACEA A3 • ACEA B3 • API SL

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

MB 229.1

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,865 g/cm ³ DIN 51757
Viscosity at 40 °C	95,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	160 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % ASTM D 5800-08 Method B

Technical data

Flash point	230 °C DIN ISO 2592
Total base number	10,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 - 1,5 g/100g
Color number (ASTM)	L 4,0 DIN ISO 2049

Areas of application

For gasoline and diesel engines with and without charge air cooling. Suitable for extended oil change intervals and high engine loads.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effectiveness only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	2338 BOOKLET
4 l Canister plastic	8998 BOOKLET
5 l Canister plastic	2536 BOOKLET
20 l Canister plastic	2537 D-GB
60 l Black plate barrel	2101 D-GB
205 l Black plate barrel	2102 D-GB
1.000 l Container	21581 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.