### **Product information**

# Central Hydraulic System Oil 2400



#### **Description**

LIQUI MOLY central hydraulic system oils meet the highest technical requirements and are suitable for a wide range of automotive applications. The carefully selected formulations made from the best raw materials ensure excellent temperature properties and guarantee the full function of the systems even at the lowest temperatures of up to -45 °C. All central hydraulic system oils are impressive thanks to excellent wear, aging and corrosion protection as well as optimum friction values and minimal foaming tendency.



manufacturer's specifications, also required in commercial vehicles for trailing axle lifting devices and cab tilting devices.

PI 30/02/28/2024

#### **Properties**

- very good low-temperature properties
- high wear resistance
- optimum stability to aging
- outstanding corrosion protection
- excellent viscosity/temperature properties

#### Specifications / Approvals

ISO 7308

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

IVECO 18-1823 Klasse 1 • LHM-Plus • Peugeot Citroen (PSA) B71 2710

#### **Technical data**

Density at 15 °C 0,855 g/cm<sup>3</sup>

DIN 51757

Viscosity at 40 °C 20,6 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at 100 °C 6,4 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -40 °C <20000 mPas

DIN 51398

Viscosity index 300

**DIN ISO 2909** 

Flash point 120 °C

**DIN ISO 2592** 

Pour point -66 °C

**DIN ISO 3016** 

Color/appearance grün

#### Areas of application

This mineral hydraulic fluid is specially adapted to the requirements of the Peugeot/Citroën PSA Group and is suitable for systems such as hydraulic brakes, level controls, steering systems, etc. Miscible with older mineral LHM formulations. Depending on the

## Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. This oil can also be used for refilling in systems. Optimum effect only when the product is used unmixed.

#### Available pack sizes

1 l Can plastic 3666

D-GB-I-E-P

1 l Can plastic 20979

GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.